

TRUSTED WHEN THE SHOW MUST GO ON.

While other show motors are out of commission for brake service or regular repairs, the TNER Krewmate theatrical chain hoist is ready when duty calls. That's because it's built using the latest technology, powered by innovative design and manufacturing processes, and backed by outstanding customer support when you need it.





FEATURES



Self-Adjusting, Reliable Pull Rotor Brake

This is the world's most reliable theatrical hoist brake - it even comes with a five-year warranty. Its simple design has no brake coil to fail or discs to replace, which keeps this hoist working longer with less maintenance.

Heavy cast iron construction gives you improved wear as the chain is quietly and smoothly guided into the chain bag. Less friction means minimal maintenance and repair.





Carbon friction material gives the TNER Krewmate consistent performance even in a wide range of temperatures. Our clutch also protects the hoist from damage and prevents overwinding.

Non-Drip Grease Packed Gears

For demanding theatrical applications, these maintenance-free, grease packed gears work to provide years of smooth, quiet operation.



- Sleek rounded body with no sharp edges
- 2 Flexible, soft-grip handles
- 3 Swivelling top and bottom hooks with heavy-duty hook latches
- 4 Complies with BGV-D8 standard
- 5 Quick-switch voltage changer
- 6 Compact size and speeds matching industry standards
- Heavy-duty motor for increased performance and durability
- 8 Black canvas chain container to meet BGV-D8 regulations
- 9 Grease-packed, heat-treated gears for a quiet and smooth operation
- Low-profile upper/lower limit switches no adjustments required
- 11 Nickel-plated load chain meets DIN and EN 818-7 standards
- Emergency stop on optional pendant (pickle)

EKREWMATE OPTIONS





- Road Case
 Provides easy transportation and hoist storage.
- Optional Push Button Pendant (Pickle)
 Available for hoist operation and includes up, down, and emergency stop functions.
- 3 Bullard Hooks
 Offers a positive locking latch feature.
- 4 Supply Cords
 Connectors for both power supply cord and push button cord for quick installation.
- **5** Black Chain Provides extra low visibility.



COMPLIANCE

Kito's theatrical chain hoists are engineered to comply with BGV-D8 standards.



D8

STANDARD HOIST SPECIFICATIONS

Capacity Range: Duty Cycle: Chain Container: 1/2 Ton - 2 Ton 30 Minutes Standard Canvas

Reconnectable Voltage: Classification: Standard Lift:

208-230/460-3-60 ASME H3, JS/ISO M3, FEM 1Bm 60' (other lengths available)

Control Voltage: Ratings: Standard Pendant and Power

110V Hoist - IP55 Supply Cord:

Optional Pendant - NEMA 4X 2.5' (longer lengths available)

WARRANTY

The product must be used in accordance with the manufacturer's recommendations and must not have been subject to abuse, lack of maintenance, misuse, negligence, or unauthorized repairs or alterations. Should any defect in material or workmanship occur during the warranted period, as determined by inspection of the product, Kito Canada Inc. agrees, at its discretion, to either replace or repair the part or product.

The customer must obtain a Return Goods Authorization as directed by Kito Canada Inc. prior to shipping the product for warranty evaluation, and an explanation of the complaint must accompany the product. Upon repair, the product will be covered for the remainder of the original warranty period. Replacement parts installed after the original warranty period will be eligible for replacement for one year from the installation date.



Please contact Kito Canada Inc. for more information or assistance. All specifications, dimensions, and drawings available online.

WWW.KITO.CA

1.888.322.KITO (5486)

WESTERN CANADA

309-3815 1ST AVE BURNABY, BC V5C 3V6



EASTERN CANADA

4-3660 ODYSSEY DR MISSISSAUGA, ON L5M 0Y9